



B217278

## TeSys motorskydds brytare 0,25-0,4

Artikelnummer: GV2ME03

E-nummer: 3116504

EAN 13-kod: 3389110342994

### Teknisk information

#### ► Certifications and standards

##### normes

CSA C22-2 No 14-05

EN 60204

IEC 60947-1

IEC 60947-2

IEC 60947-4-1

NF C 63-120

NF C 63-650

NF C 79-130

UL 508

VDE 0113

VDE 0660

##### product certifications

ATEX

BV

CCC

CEBEC

CSA

DNV (Det Norske Veritas)

EZU

gL

GOST

LROS (Lloyds register of shipping)

PTB

RINA

SETI

TSE

UL

#### ► Connections

##### connections - terminals

 screw clamp terminal 2 cable 1 - 4 mm<sup>2</sup> - cable stiffness: flexible - with cable end

 screw clamp terminal 2 cable 1 - 6 mm<sup>2</sup> - cable stiffness: solid

 screw clamp terminal 2 cable 1,5 - 6 mm<sup>2</sup> - cable stiffness: flexible - without cable end

#### ► Electrical

##### Nätfrekvens

50/60 Hz

##### Motor effekt kW

0,09 kW at 400...415 V AC 50/60 Hz

##### [In] rated current

0,4 A

##### Ström magnetiskt utlösning

5 A

##### phase failure sensitivity

yes conforming to IEC 60947-4-1 § 7-2-1-5-2

##### [Ue] rated operational voltage

600 V AC 50/60 Hz conforming to CSA C22-2 No 14

600 V AC 50/60 Hz conforming to UL 508

[Ui] rated insulation voltage	690 V AC 50/60 Hz conforming to IEC 60947-2 600 V conforming to CSA C22-2 No 14 600 V conforming to UL 508 690 V conforming to IEC 60947-2
[Ith] conventional free air thermal current Nätfrekvens	0,4 A conforming to IEC 60947-4-1 50/60 Hz conforming to CSA 50/60 Hz conforming to IEC 60947-4-1 50/60 Hz conforming to UL
[Uimp] rated impulse withstand voltage power dissipation per pole rated duty Brytförmåga	6 kV conforming to IEC 60947-2 2,5 W continuous conforming to IEC 60947-4-1 Icu > 100 kA at 230...240 V AC 50/60 Hz conforming to IEC 60947-2 Icu > 100 kA at 400...415 V AC 50/60 Hz conforming to IEC 60947-2 Icu > 100 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 Icu > 100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 Icu > 100 kA at 690 V AC 50/60 Hz conforming to IEC 60947-2
<b>► Environment</b>	
protective treatment	TH
IP degree of protection	IP20 open mounted conforming to IEC 60529
Shockbeständighet	30 gn 11 ms conforming to IEC 60068-2-27
ambient air temperature for operation	-20 - 40 °C in enclosure -20 - 60 °C open mounted
ambient air temperature for storage	-40 - 80 °C
fire resistance	960 °C conforming to IEC 60695-2-1
operating altitude	<= 2000 m
hållbarhet mot mekanisk påverkan	0,5 J open mounted
<b>► Functional</b>	
Manövertyp	tryckknapp
Termiskt överströmsrelä, inställningsområde	0,25 - 0,4 A conforming to IEC 60947-4-1
maximum number of switchings	25 cyc/h
<b>► Installation</b>	
Montagesätt	fast
mounting support	rail
mounting position	horisontell vertikal
<b>► Performance</b>	
mechanical durability	100000 cycles
electrical durability	100000 cycles on AC-3 at 440 V In/2
[Ics] rated service short-circuit breaking capacity	> 100 % at 230...240 V AC 50/60 Hz conforming to IEC 60947-2 > 100 % at 400...415 V AC 50/60 Hz conforming to IEC 60947-2 > 100 % at 440 V AC 50/60 Hz conforming to IEC 60947-2 > 100 % at 500 V AC 50/60 Hz conforming to IEC 60947-2 > 100 % at 690 V AC 50/60 Hz conforming to IEC 60947-2
<b>► Physical characteristics</b>	
tightening torque	1,7 N.m - on screw clamp terminal - cable 1 - 4 mm <sup>2</sup> 1,7 N.m - on screw clamp terminal - cable 1 - 6 mm <sup>2</sup> 1,7 N.m - on screw clamp terminal - cable 1,5 - 6 mm <sup>2</sup>
Höjd	89 mm
Bredd	44,5 mm
Inbyggnadsdjup mm	78,2 mm
vikt	0,26 kg
<b>► Poles descriptions</b>	
Polbeskrivning	3P
<b>► Product identification</b>	
range of product	GV2ME

Enhets korta namn

thermal magnetic circuit breaker

► **Usage / Application**

Brytarapplikation

motor skydd

Typ av nät

AC

suitability for isolation

yes conforming to IEC 60947-1 § 7-1-6

utilisation category

AC-3 conforming to IEC 60947-4-1

category A conforming to IEC 60947-2

**Leverantörsinformation**

Leverantör: Schneider Electric Sverige AB

Fax: +46 155 26 54 91

Webb: <http://www.schneider-electric.se>

Adress: Eskilstunavägen 7, 611 56 Nyköping

Tel: +46 155 26 54 00

e-Post: [info@se.schneider-electric.com](mailto:info@se.schneider-electric.com)